



Model PT-7010A Front

Introducing an innovative and elegant, fully-featured two-zone pre/pro/tuner: Model PT-7010A.

From the beginning, our philosophy has been to concentrate our efforts on the design, engineering and marketing of audio and audio/video components with rugged build quality, high-performance and innovative features at affordable prices. With an exceptional pedigree as our keystone, Sherbourn products have been recognized and praised around the world by discerning consumers and knowledgeable industry commentators.

To complement our line of Home Theater Amplifiers, including our legendary 2.1kW, model 7/2100A with its seven toroidal transformers, seven mono blocks and two power cords, we now offer a Pre/Pro/Tuner with an unrivalled value for performance that will let you enjoy film soundtracks and music with a fidelity unmatched by today's receivers. With an aesthetic design that matches any of our seven or five channel amplifiers beautifully, the new PT-7010A is perfect for the discerning customer seeking high performance with a pleasing design.



Model PT-7010A Rear

FEATURES AND SPECIFICATIONS: PT-7010A PRE/PRO/TUNER

- 24-bit, Crystal Semiconductor® analog-to-digital converter and 24-bit, 192 KHz Analog Devices® digital-to-analog converters
- 32-bit, 20 Mhz control processor
- 24-bit, 150 MIPS Motorola Symphony™ DSP processor
- Dolby Digital EX, Dolby Pro Logic 2, Dolby Pro Logic 2X, DTS ES and DTS NEO: 6 decoding modes
- Support for all digital sampling rates to 96 KHz
- Digital Domain treble and bass control as well as bass management function
- DSP “simulated” surround mode for enhancement of two-channel source
- Direct two-channel analog bypass mode
- Gold-plated input and output connectors and balanced XLR outputs and unbalanced RCA outputs
- Six A/V inputs, each with audio, S-video and composite video with three A/V outputs, each with audio, S-video and composite video
- Eight-channel analog input with separate RCA connectors for DVD-audio format
- Three component video inputs and two component video outputs
- Automatic video transcoding: up converts composite and S-video source-to-component video
- Six coaxial and four digital inputs and coaxial and optical digital outputs, including from analog and down mixed 5.1 sources
- AM/FM tuner with 40 presets
- Three audio only inputs including MM phono stage
- Two tape outputs
- Record outputs feature down-mixed two-channel output from a 5.1 digital source
- Four sub-woofer outputs
- 7.1 channel outputs plus stereo side outputs for a total of 9.1 channels
- Party mode for two-channel playback through all speakers
- Zone Two can play sources independent of the main zone
- Trigger outputs for both zones
- IR control of both zones with rear IR ports and discrete codes
- RS-232 control port with discrete codes
- Flash memory upgradable through RS-232 port
- IEEE 1394 Firewire port for future expansion

SPECIFICATIONS:

Carton weight	38 lbs/17.3 kilograms
Dimensions	17.75" W x 15.75" D x 5.875"H

SHERBOURN TECHNOLOGIES INC.
19/3A Sterling Road • North Billerica, MA 01862 USA

Tel: 978-663-7385 Fax: 978-663-7389
www.Sherbourn.com

SPECIFICATIONS